



Product Brief

JMS581SD USB 3.2 Gen2x1 to SD Express Bridge Controller

Document No.: PDB-00000007 / Revision: 1.01 / Date: 24/04/2020

JMicron Technology Corporation

1F, No. 13, Innovation Road 1, Science-Based Industrial Park,
Hsinchu, Taiwan 300, R.O.C.

Tel: 886-3-5797389

Fax: 886-3-5799566

Email: sales@jmicron.com

Website: <http://www.jmicron.com>

Copyright © 2019, JM Micron Technology Corp. All Rights Reserved.

Printed in Taiwan 2019

JMicron and the JM Micron Logo are trademarks of JM Micron Technology Corporation in Taiwan and/or other countries.

Other company, product and service names may be trademarks or service marks of others.

All information contained in this document is subject to change without notice. The products described in this document are NOT intended for use implantation or other life supports application where malfunction may result in injury or death to persons. The information contained in this document does not affect or change JM Micron's product specification or warranties. Nothing in this document shall operate as an express or implied license or environments, and is presented as an illustration. The results obtained in other operating environments may vary.

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED ON AN "AS IS" BASIS. In no event will JM Micron be liable for damages arising directly or indirectly from any use of the information contained in this document.

For more information on JM Micron products, please visit the JM Micron web site at <http://www.JMicron.com> or send e-mail to sales@jmicron.com.

JMicron Technology Corporation

1F, No.13, Innovation Road 1, Science-Based Industrial Park, Hsinchu, Taiwan 300, R.O.C.

Tel: 886-3-5797389

Fax: 886-3-5799566

Revision History

Revision number	Effective date	Description of revision		Author
		Reference	Description of change	
1.00	20/01/2020	--	Initial release	Larry Chien
1.01	24/04/2020	Section 5	Modify the package dimension	Katrina Mo

Table of Contents

Revision History	2
Table of Contents	3
1 Overview	4
2 Features	5
2.1 General Features.....	5
2.2 Universal Serial Bus.....	5
2.3 SD Express.....	5
3 Block Diagram	6
4 Application	7
5 Package Dimension	8

Figure List

Figure 1 Block Diagram – JMS581SD	6
Figure 2 Application Scenarios	7
Figure 3 Package Outline Drawing of 144TFBGA 9x9mm²	9

1 Overview

JMS581SD is a system on chip solution which embedded with USB 3.2 Gen2x1 10Gb/s to SD Express interfaces. Its upstream port provides a USB which data speed can reach up to 10Gb/s. Meanwhile, its downstream port can connect to UHS-1 and SD Express memory card. SD Express port can achieve up to maximum 985MB/s data transfer rate. Meanwhile, JMS581SD can backward compatible with legacy SD cards.

Moreover, JMS581SD has USB Type-C™ connectivity built in to the controller that any device using JMS581SD can have a USB Type-C™ connector without adding any additional peripheral part. It can save costs to buy parts, and efforts to build inventory, and it can reduce printed circuit board area for the system designs.

JMS581SD supports TRIM to the NAND flash based storages and enable transmit and receive data by both of the USB Mass Storage Class Bulk-Only Transport (BOT) and USB Attached SCSI Protocol (UASP) to and from the host respectively. The data storage devices can achieve its summit of performance by taking advantage of these built-in unmatched features.

2 Features

2.1 General Features

- Design for Windows 7, Windows 10 and MAC 10.10.5 or later version
- Provide 8 hardware controlled PWMs
- Provide software utilities for downloading the upgraded firmware code under USB2.0/ USB3.2 Gen1 and USB3.2 Gen2
- 144TFBGA (9x9mm²) package
- Support 25MHz external crystal
- Support 3.3V I/O
- 32 GPIOs for customization

2.2 Universal Serial Bus

- Comply with USB 3.2 Gen 1 and Gen 2 Specification,
- Comply with USB Mass Storage Class, Bulk-Only Transport Specification (Revision 1.0)
- Comply with USB Attached SCSI Protocol (UASP) Specification (Revision 4)
- Integrate with USB Type-C™ multiplexer & configuration channel (CC) logic
- Support USB Super-Speed/ High-Speed/ Full-Speed Operation
- Support USB2.0/ USB 3.2 Gen 1/ Gen 2 power saving mode
- Support external SPI NVRAM for Vendor VID/PID of USB2.0/USB 3.2 Gen 1/2 device controller

2.3 SD Express

- Support SD 3.01 UHS-1
- Support SD 7.1 SD Express (PCIe Gen3x1 NVMe 1.3)

3 Block Diagram




Figure 1 Block Diagram – JMS581SD

4 Application







Figure 2 Application Scenarios

5 Package Dimension

Symbol	Dimension in mm			Dimension in inch		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.03	1.10	1.17	0.041	0.043	0.046
A1	0.16	0.21	0.26	0.006	0.008	0.010
A2	0.84	0.89	0.94	0.033	0.035	0.037
c	0.32	0.36	0.40	0.013	0.014	0.016
D	8.90	9.00	9.10	0.350	0.354	0.358
E	8.90	9.00	9.10	0.350	0.354	0.358
D1	----	8.25	----	----	0.325	----
E1	----	8.25	----	----	0.325	----
e	----	0.75	----	----	0.030	----
b	0.25	0.30	0.35	0.010	0.012	0.014
aaa	0.15			0.006		
ccc	0.10			0.004		
ddd	0.08			0.003		
eee	0.15			0.006		
fff	0.08			0.003		
MD/ME	12/12					

NOTE :

1. CONTROLLING DIMENSION : MILLIMETER.
2. PRIMARY DATUM C AND SEATING PLANE ARE DEFINED BY THE SPHERICAL CROWNS OF THE SOLDER BALLS.
3. DIMENSION b IS MEASURED AT THE MAXIMUM SOLDER BALL DIAMETER, PARALLEL TO PRIMARY DATUM C.
4. SPECIAL CHARACTERISTICS C CLASS: ccc,ddd(SPIL STANDARD)
5. THE PATTERN OF PIN 1 FIDUCIAL IS FOR REFERENCE ONLY.
6. REFERENCE DOCUMENT : JEDEC PUBLICATION 95 DESIGN GUIDE 4.5






Figure 3 Package Outline Drawing of 144TFBGA 9x9mm²

How to Reach Us:

- Home Page: <http://www.jmicron.com>
- Technical & Order Support: sales@jmicron.com

A series of light gray, stylized circuit traces or data lines that flow across the bottom of the page, starting from the left and moving towards the right, eventually merging into the blue and green gradient bar.

<http://www.jmicron.com>



JMicron
Storing the World · Bridging the Future