



Product Brief

JMS581LT USB 3.2 Gen2x1 to SATA 6Gb/s, PCIe G3x2 & SD Express Bridge Controller

Document No.: PDB-00000004 / Revision: 1.00 / Date: 20/01/2020

JMicron Technology Corporation

1F, No. 13, Innovation Road 1, Science-Based Industrial Park,
Hsinchu, Taiwan 300, R.O.C.

Tel: 886-3-5797389

Fax: 886-3-5799566

Email: sales@jmicron.com

Website: <http://www.jmicron.com>

Copyright © 2019, JMicon Technology Corp. All Rights Reserved.

Printed in Taiwan 2019

JMicon and the JMicon Logo are trademarks of JMicon Technology Corporation in Taiwan and/or other countries.

Other company, product and service names may be trademarks or service marks of others.

All information contained in this document is subject to change without notice. The products described in this document are NOT intended for use implantation or other life supports application where malfunction may result in injury or death to persons. The information contained in this document does not affect or change JMicon's product specification or warranties. Nothing in this document shall operate as an express or implied license or environments, and is presented as an illustration. The results obtained in other operating environments may vary.

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED ON AN "AS IS" BASIS. In no event will JMicon be liable for damages arising directly or indirectly from any use of the information contained in this document.

For more information on JMicon products, please visit the JMicon web site at <http://www.JMicon.com> or send e-mail to sales@jmicon.com.

JMicon Technology Corporation

1F, No.13, Innovation Road 1, Science-Based Industrial Park, Hsinchu, Taiwan 300, R.O.C.

Tel: 886-3-5797389

Fax: 886-3-5799566

Revision History

Revision number	Effective date	Description of revision		Author
		Reference	Description of change	
1.00	20/01/2020	--	Initial release	Larry Chien

Table of Contents

Revision History	2
Table of Contents	3
1 Overview	4
2 Features	5
2.1 General Features	5
2.2 Universal Serial Bus	5
2.3 PCI Express	5
2.4 Serial ATA	5
2.5 SD Express	5
3 Block Diagram	6
4 Application	7
5 Package Dimension	8

Figure List

Figure 1 Block Diagram – JMS581LT	6
Figure 2 Application Scenarios	7
Figure 3 Package Outline Drawing of 144TFBGA 9x9mm ²	9

1 Overview

JMS581LT is a system on chip solution which embedded with USB 3.2 Gen2x1 10Gb/s, SATA 6Gb/s, PCIe/ NVMe Gen 3x2, and SD Express. Its upstream port provides a USB which data speed can reach up to 10Gb/s. Meanwhile, its downstream port can connect to SATA/ PCIe NVMe/ SD Express storage devices, such as a hard drive, solid-state drive, CFast/CF Express/ SD Express memory card. The data speed for SATA port can reach 6Gb/s, or the data rate for the SATA III requirement. The PCIe port can reach 16Gb/s, or the data rate for the PCIe Gen3x2 requirements. The SD Express port can reach maximum 985 MB/s data transfer rate.

Moreover, JMS581LT has USB Type-C™ connectivity built in to the controller that any device using JMS581LT can have a USB Type-C™ connector without adding any additional peripheral part. It can save costs to buy parts, and efforts to build inventory, and it can reduce printed circuit board area for the system designs.

JMS581LT supports TRIM to the NAND flash based storages and enable transmit and receive data by both of the USB Mass Storage Class Bulk-Only Transport (BOT) and USB Attached SCSI Protocol (UASP) to and from the host respectively. The data storage devices can achieve its summit of performance by taking advantage of these built-in unmatched features.

JMS581LT is well equipped for power management that it can meet a wide variety of power requirements from different scales of data storage systems: those for all-in-one card reader, docking station and portable storage applications.

Owing to its USB Type-C™ connectivity, JMS581LT can work with some power management controllers to a USB Power Delivery (PD) enabled data storage device. The data storage devices having SSDs of large capacity can accept the electrical power from sources of energy, such as hosts acting as a power provider of USB PD to supply sufficient electricity to the device after they negotiate with each other, without plugging in.

2 Features

2.1 General Features

- Design for Windows 7, Windows 10 and MAC 10.10.5 or later version
- Provide 8 hardware controlled PWMs
- Provide software utilities for downloading the upgraded firmware code under USB2.0/ USB3.2 Gen1 and USB3.2 Gen2
- 144TFBGA (9x9mm²) package
- Support 25MHz external crystal
- Support 3.3V I/O
- 32 GPIOs for customization

2.2 Universal Serial Bus

- Comply with USB 3.2 Gen 1 and Gen 2 Specification,
- Comply with USB Mass Storage Class, Bulk-Only Transport Specification (Revision 1.0)
- Comply with USB Attached SCSI Protocol (UASP) Specification (Revision 4)
- Integrate with USB Type-C™ multiplexer & configuration channel (CC) logic
- Support USB Super-Speed/ High-Speed/ Full-Speed Operation
- Support USB2.0/ USB 3.2 Gen 1/ Gen 2 power saving mode
- Support external SPI NVRAM for Vendor VID/PID of USB2.0/USB 3.2 Gen 1/2 device controller

2.3 PCI Express

- Comply with PCI Express Base Specification Revision 3.1a
- Comply with NVM Express 1.3
- Support TRIM to the SSD

2.4 Serial ATA

- Comply with SATA Specification (Revision 3.1)
- Support TRIM to SATA
- Support Native Command Queue (NCQ)

2.5 SD Express

- Support SD 3.01 UHS-1
- Support SD 7.1 SD Express (PCIe Gen3x1 NVMe 1.3)
- Support TRIM to SD 7.1

3 Block Diagram




Figure 1 Block Diagram – JMS581LT

4 Application

Typical Applications (JMS581LT)






Figure 2 Application Scenarios

5 Package Dimension



TITLE : 144LD TFBGA (9X9mm) PACKAGE OUTLINE



Symbol	Dimension In mm			Dimension In Inch		
	MIN	NOM	MAX	MIN	NOM	MAX
A	---	---	1.20	---	---	0.047
A1	0.16	0.21	0.26	0.006	0.008	0.010
A2	0.84	0.89	0.94	0.033	0.035	0.037
c	0.32	0.36	0.40	0.013	0.014	0.016
D	8.90	9.00	9.10	0.350	0.354	0.358
E	8.90	9.00	9.10	0.350	0.354	0.358
D1	---	8.25	---	---	0.325	---
E1	---	8.25	---	---	0.325	---
e	---	0.75	---	---	0.030	---
b	0.25	0.30	0.35	0.010	0.012	0.014
aaa	0.10			0.004		
bbb	0.20			0.008		
ccc	0.12			0.005		
ddd	0.15			0.006		
eee	0.08			0.003		
MD/ME	12/12			12/12		

DETAIL : "B"

- NOTE :
1. CONTROLLING DIMENSION : MILLIMETER.
 2. PRIMARY DATUM C AND SEATING PLANE ARE DEFINED BY THE SPHERICAL CROWNS OF THE SOLDER BALLS.
 3. DIMENSION b IS MEASURED AT THE MAXIMUM SOLDER BALL DIAMETER, PARALLEL TO PRIMARY DATUM C.
 4. REFERENCE DOCUMENT : JEDEC MO-216
 5. THE PATTERN OF PIN 1 FIDUCIAL IS FOR REFERENCE ONLY.
 6. SPECIAL CHARACTERISTICS C CLASS: bbb, ccc

Figure 3 Package Outline Drawing of 144TFBGA 9x9mm²

How to Reach Us:

- Home Page: <http://www.jmicron.com>
- Technical & Order Support: sales@jmicron.com

A series of thin, light gray lines that resemble circuit traces or data paths, starting from the left and moving towards the right, with some lines curving upwards and others downwards, creating a sense of movement and connectivity.

<http://www.jmicron.com>



JMicron
Storing the World · Bridging the Future